

im importuser

[imports one or more users into Integrity](#)

SYNOPSIS

```
im importuser [--[no]allowNonRealm] [--hostname=server] [--port=number] [--password=password] [--user=name]  
[(-?|--usage)] [(-F file|--selectionFile=file)] [(-N|--n)] [(-Y|--yes)] [--[no]batch] [--cwd=directory]  
[--forceConfirm=[yes/no]] [-g | --gui] [--quiet] [--settingsUI=[gui/default]] [--status=[none/gui/default]] string...
```

DESCRIPTION

im importuser imports one or more users into the Integrity database. This command is helpful for adding users who have not yet auto-registered by logging in, or for adding a number of users at one time. Additionally, you can import non-realm users by specifying a large user list text file. For example:

```
im importuser jriley
```

imports the user *jriley*.

Options

This command takes the universal options available to all **im** commands, as well as some general options. See the [options](#) reference page for descriptions.

--[no]allowNonRealm

specifies whether to import users that are not part of the security realm. **--noallowNonRealm** is specified by default.

Note: Importing non-realm users creates new user principals.

string...

specifies the names of one or more users to import.

SEE ALSO

Commands:

[im importgroup](#), [im importissue](#), [im creategroup](#), [im createuser](#)

Miscellaneous:

[options](#)